


Wood Floor Specification Sheet

3/4" Engineered European Oak - Smoked



Quercus Robar is sourced from managed forests by our FSC certified mill in Europe. Logs are French Cut and the lamellas are graded to our custom specification. The sawn lamellas are bonded to an exterior grade Baltic birch substrate, precision milled, filled as necessary, and sanded smooth.

Janka Hardness: 1360

Grade Options: Prime or Light Rustic Plank Width Options: 7" (180mm) Custom inquire

*Imperial dimensions are approximate

Standard Lengths: 2' - 10' (600mm - 3000mm) || Long Length 11'-13' inquire

Thickness Options: %" with 6mm Sawn Wear Layer
Profile: Tongue + Groove & End Matched
Edges: Eased Edge 4 Sides || Square Edged

Core: Engineered, Marine Grade (exterior grade) Baltic Birch Plywood

Adhesive: Top Layer Lamination – Cold Press, Exterior Grade

Multibond SK-8 (ie – Titebond III Wood Glue) Plywood – Phenolic by Dynea, Exterior Grade

Product Contains No Added Urea Formaldehyde (NAUF)
CARB ACTM Phase II Compliant (← 0.05PPM Formaldehyde)

Finish Options: UV Bona Polyurethane || UV Cured Oil || UV Cured Hardwax || Unfinished

Treatment Options: Wire Brush (Light, Medium, or Heavy)

Single Smoke (Fumed) Double Smoke Hand Scraped Custom Distressed

Fire Treatment (ASTME 84)

Floor Score#: SCS-FS-6135

FSC: Available Upon Request

ANSI Accredited: ISO/IEC 17065

Indoor Air Quality Cert: SCS-EC10.3-2014v4.0

Warranties: Structural – Lifetime Warranty (see documentation on website or contact your representative)

Installation: Follow NWFA + Manufacturer Guidelines for Installation + Environmental Conditions.